Hall D WEDM

Date: July 17, 2019

DSG Staff: *Peter Bonneau, Pablo Campero, Tyler Lemon*

1. Screens requested by Hall D to be converted to WEDM and their status:
    1.1. BCAL Chillers – complete
    1.2. Beamline Vacuum – complete
    1.3. ComCal Environment – complete
    1.4. ComCal Chiller – complete
    1.5. DIRC Environment – complete
    1.6. Hall Environment Conditions – complete
    1.7. Main Gas System – complete
    1.8. Tagger NMR – complete
    1.9. Solenoid Cryogenics – complete
    1.10. Solenoid Coil 2 Temperatures – complete
    1.11. Solenoid Coil 1 Temperatures – complete
    1.12. Solenoid Coil 3 Temperatures – complete
    1.13. Solenoid Coil 4 Temperatures – complete
    1.14. Solenoid Interlocks – complete
    1.15. Solenoid Strain Gauges – complete
    1.16. Solenoid Vacuum Pumps – complete
    1.17. Solenoid Voltage Taps – complete
    1.18. FDC Chiller – on hold
    1.19. Solenoid Power Supply – on hold

2. To be able to complete FDC Chiller and Solenoid Power Supply screens, individual PVs will need to be added to IOC by Hall D for status bits.
    2.1. CSS screen uses local PVs for status bits parsed from a main array using a script   and WEDM cannot utilize embedded scripts.

3. Completed screens located at https://epicsweb.jlab.org/wedm/browse?dir=/cs/opshome/edm/hld

4. Hall D screens to added to *epicsweb*'s WMenu.
    4.1. Menu path: Main Menu → Standalone Menu → Hall D Standalone Menus → Hall D Detector Components.