



Detector Support Group

We choose to do these things "not because they are easy, but because they are hard".

Weekly Report, 2021-11-24

Summary

Hall A – SoLID

Mary Ann Antonioli, Pablo Campero, Brian Eng, Mindy Leffel, and Marc McMullen

- Wiring instrumentation racks #1 and #2
 - ★ Wired motor controller relay board, Dataforth module (including breakout board for vacuum, liquid levels, and pressure transducer signals), and 13 PLC terminal blocks
- Continued modeling SoLID instrumentation racks using NX12
 - ★ Modeled parts for DIN railing, Motor Controller board, and assembled models for signal conditioners
- Developing index detailing number of sheets per drawing for all developed drawings
- Fabricated 20 ferrule-to-ferrule cables

Hall B – RICH-II


Mary Ann Antonioli, Peter Bonneau, Pablo Campero, Brian Eng, George Jacobs, Tyler Lemon, and Marc McMullen

- Reevaluating rotation forces on winch for detector assembly
 - ★ Calculation necessary for safety approval of lift plan
 - ★ Repeated calculation by hand
 - ★ Starting to perform calculation in Ansys
 - RICH detector and assembly structure model imported into Ansys and going through process of generating meshes for all items
- Submitted procurement requests for RICH hardware interlock system components
- Revising safety documents – lift plan is being modified to account for weight added by stiffening tool (625 lbs.)
- Fabricated 13 Molex cables needed to connect sensors to hardware interlock chassis backplane
- Populating backplane PCB

Hall C – NPS

Mary Ann Antonioli, Peter Bonneau, Aaron Brown, Pablo Campero, Brian Eng, George Jacobs, Mindy Leffel, Tyler Lemon, and Marc McMullen

- Developed Python script to generate *Hall C NPS* Phoebus screen
 - ★ Screen features an embedded display for each PMT channel, made by Mary Ann, with a power status LED and readback voltage and current
 - ★ Each embedded display is overlaid with a transparent action button that, when clicked, opens a pop-up window for PMT settings, also made by Mary Ann, where user can set voltage and current limit for a channel




Screenshot of *Hall C NPS* Phoebus screen

- Developing Python script to generate voltage and current stability plots for each channel of a module to be included in the DSG testing & analysis MariaDB database
- Worked on ESR foil pre-shaping – 320 of 600 completed (~53%)

EIC

Pablo Campero, Brian Eng

- Manually calculated heat generated and temperature for the silicon sensor L1
 - ★ Calculations done based on $T_{\text{surface}} = (Q/mc) + T_{\text{ambient}}$
 - ★ Convective heat transfer Q to Si L1 inner surface given by Ansys is 11.71 W
 - ★ Calculations, done every 0.2 s, indicate needing ~30 s to reach 100°C on Si L1



- Started simulation of the flow using Ansys *Fluid Flow*
 - ★ Generated enclosure for the model



Detector Support Group

We choose to do these things "not because they are easy, but because they are hard".

Weekly Report, 2021-11-24

Antonioli, Mary Ann

Vacation


Bonneau, Peter

Vacation

Brown, Aaron

Hall C – NPS

- Developed Python script to generate *Hall C NPS* Phoebus screen
 - ★ Screen features an embedded display for each PMT channel, made by Mary Ann, with a power status LED and readback voltage and current
 - ★ Each embedded display is overlaid with a transparent action button that when clicked opens a pop-up window for PMT settings, also made by Mary Ann, where user can set voltage and current limit for a channel



- Developing Python script to generate voltage and current stability plots for each channel of a module to be included in the DSG testing & analysis MariaDB database

DSG

- Attended daily meetings for DSG Projects
- Held weekly DSG-NPS R&D meeting
- Compiled, edited, and posted Weekly Report



Detector Support Group

We choose to do these things "not because they are easy, but because they are hard".

Weekly Report, 2021-11-24


Campero, Pablo

Hall A – SoLID

- With Mindy, worked on instrumentation racks' (#1 and #2) wiring for magnet control system
 - ★ Wired motor controller relay board
 - ★ Wired Dataforth module including breakout board for vacuum, liquid levels, and pressure transducer signals
 - ★ Wired 13 PLC terminal blocks
- Updated *Cable Information* spreadsheet
- With Mary Ann, working on the index sheet (detailing number of sheets/drawing) for all developed drawings

EIC – Thermal Analysis

- Manually calculated heat generated and temperature for the silicon sensor L1
 - ★ Calculations done based on $T_{\text{surface}} = (Q/mc) + T_{\text{ambient}}$
 - ★ Convective heat transfer Q to Si L1 inner surface given by Ansys is 11.71 [W]
 - ★ Calculation done every 0.2 s
 - ★ Calculations indicate need ~30 s to reach 100°C on Si L1






Detector Support Group

We choose to do these things "not because they are easy, but because they are hard".

Weekly Report, 2021-11-24



- Started simulation of the flow by using Ansys *Fluid Flow*
 - ★ Generated enclosure for the model

DSG

- Attended to the DSG projects status meetings
- Arranged meetings and generated meeting minutes to discuss the progress of the SoLID Magnet Controls project

Eng. Brian

Vacation

Jacobs, George

Vacation

Leffel, Mindy

Hall A – SoLID

- Fabricated 20 cables (ferrule-to-ferrule)
- Worked with Pablo wiring racks

Hall B – RICH-II

- Started populating backplane PC board
- Fabricated 13 Molex cables (hardware interlock chassis backplane to sensors)

Hall C – NPS

- Reflective film pre-shaping: completed 50, 180 to date; total 320

DSG

- Attended weekly meetings

Lemon, Tyler

Hall B – RICH-II

- Writing note on hardware interlock chassis design in NX12



Detector Support Group

We choose to do these things "not because they are easy, but because they are hard".

Weekly Report, 2021-11-24

- Submitted procurement requests (PRs) for RICH hardware interlock system components
 - ★ PR 408047P – nylon standoffs for PCBs, banana plugs for connecting external ground to chassis' RJ45 ports' shield, gas system sensor USB feedthroughs, and gas system sensors USB and D-Sub connectors
 - ★ PR 408048 – screws and nuts for mounting PCBs to chassis
 - ★ PR 408050 – 100-ft flat, CAT7 cable for I²C connection between hardware interlock chassis and feedthroughs at detector
- Reevaluating rotation forces on winch for detector assembly
 - ★ Calculation necessary for safety approval of lift plan
 - ★ Repeated calculation by hand
 - ★ Starting to perform calculation in Ansys
 - RICH detector and assembly structure model imported into Ansys and going through process of generating meshes for all items

McMullen, Marc

Hall A – ECal

- Inspected one ECal Supermodule frame for assembly

Hall A – SoLID

- Continued work on SoLID rack in NX12
 - ★ Modeled parts for DIN railing, Motor Controller board, and assembled models for signal conditioners

Hall B – RICH-II

- RMC update
 - ★ Projected arrival 12/06/21
- Backplane PCB update
 - ★ Currently being assembled for testing by Mindy Leffel
- Safety documents
 - ★ Lift plan is being modified to account for weight added by stiffening tool (625 lbs)
 - ★ Strap dimensions will reflect the change in location of rigging
- Patch panel quote has been sent to INFN
 - ★ INFN has requested a final quote from GandR Metals of Newport News for fabrication
 - ★ Submitted and received quote to fabricate RICH II hardware interlock chassis

DSG/Safety

- Started proposal on multichannel gas control system